



CHARISMA



Mini CHARISMA Round



Mini CHARISMA Square



Mini CHARISMA Round

Application Type : Bollard
Subgroup : Semi shielded bollard / General bollard

Mini CHARISMA Round / 7821
Mini CHARISMA Round / 7822
Mini CHARISMA Round / 7823

Luminaire Performance

420 – 810 lm
14 W
30 – 57 lm/W

Beam Options



Color Temperature

2700K/ 3000K/ 4000K

Controller

On-Off/ 1-10V/ DALI

Input Options

220-240Vac 50/60Hz

Accessories



Anchor bolt



IP68
Connector

Mini CHARISMA Square


Application Type : Bollard
Subgroup : Semi shielded bollard / General bollard

Mini CHARISMA Square / 7824
Mini CHARISMA Square / 7825
Mini CHARISMA Square / 7826

Luminaire Performance

410 – 650 lm
14 W
29 – 46 lm/W

Beam Options



Color Temperature

2700K/ 3000K/ 4000K

Controller

On-Off

Input Options

220-240Vac 50/60Hz

Accessories



Anchor bolt



IP68
Connector



Medium CHARISMA Round



Medium CHARISMA Round














Application Type : Bollard
 Subgroup : Semi shielded bollard / Shielded bollard

Medium CHARISMA Round / 7156	
Medium CHARISMA Round / 7157	
Medium CHARISMA Round / 7859	
Luminaire Performance	
	720 - 1690 lm
	19 - 26 W
	37 - 65 lm/W
Beam Options	
Color Temperature	
	2700K/ 3000K/ 4000K
Controller	
	On-Off/ 1-10V/ DALI/ CASAMBI
Input Options	
	220-240Vac 50/60Hz
Accessories	
	Anchor bolt
	IP68 Connector



Terminal 21, Nakhon Ratchasima - THAILAND

CHARISMA

	Product Code	Luminaire Wattage	Beam	CCT	Luminaire Lumen	Efficacy	Controller				Ordering Code		
													
Mini CHARISMA Round		14 W	N/A	2700 K	730 lm	52 lm/W	•	•	•	•	7821-0-3-503-XX		
				3000 K	770 lm	55 lm/W					7821-0-3-901-XX		
				4000 K	810 lm	57 lm/W					7821-0-3-904-XX		
				3000 K	770 lm	55 lm/W					7821-0-4-901-XX		
				4000 K	810 lm	57 lm/W					7821-0-5-904-XX		
		14 W	N/A	3000 K	540 lm	38 lm/W	•				7822-0-3-901-XX		
				4000 K	570 lm	40 lm/W	•				7822-0-3-904-XX		
		14 W	N/A	2700 K	420 lm	30 lm/W	•				7823-0-3-503-XX		
				3000 K	440 lm	31 lm/W	•				7823-0-3-901-XX		
				4000 K	460 lm	32 lm/W	•				7823-0-3-904-XX		
		14 W	N/A	2700 K	590 lm	42 lm/W	•				7824-0-3-503-XX		
				3000 K	620 lm	44 lm/W	•				7824-0-3-901-XX		
				4000 K	650 lm	46 lm/W	•				7824-0-3-904-XX		
		14 W	N/A	3000 K	520 lm	37 lm/W	•				7825-0-3-901-XX		
				4000 K	550 lm	39 lm/W	•				7825-0-3-904-XX		
		14 W	N/A	3000 K	410 lm	29 lm/W	•				7826-0-3-901-XX		
				4000 K	430 lm	30 lm/W	•				7826-0-3-904-XX		
		19 W	N/A	2700 K	920 lm	48 lm/W	•				7156-0-3-506-XX		
					3000 K	970 lm	51 lm/W	•				7156-0-3-887-XX	
				4000 K	990 lm	52 lm/W	•				7156-0-3-891-XX		
		26 W	N/A	3000 K	1320 lm	50 lm/W	•				7156-0-3-902-XX		
				4000 K	1360 lm	52 lm/W	•				7156-0-3-905-XX		
		19 W	N/A	3000 K	720 lm	37 lm/W	•				7157-0-3-887-XX		
					3000 K	980 lm	37 lm/W	•				7157-0-3-902-XX	
		26 W	N/A	4000 K	1010 lm	38 lm/W	•				7157-0-3-905-XX		
				3000 K	980 lm	37 lm/W			•		7157-0-5-902-XX		
		19 W	N/A	2700 K	1150 lm	60 lm/W	•				7859-0-3-506-XX		
							3000 K	1200 lm	63 lm/W	•			7859-0-3-887-XX
							4000 K	1230 lm	64 lm/W	•			7859-0-3-891-XX
							2700 K	1150 lm	60 lm/W		•		7859-0-4-506-XX
							3000 K	1200 lm	63 lm/W		•		7859-0-4-887-XX
							4000 K	1230 lm	64 lm/W		•		7859-0-4-891-XX
					2700 K	1150 lm	60 lm/W			•	7859-0-5-506-XX		
					3000 K	1200 lm	63 lm/W			•	7859-0-5-887-XX		
					4000 K	1230 lm	64 lm/W			•	7859-0-5-891-XX		
					2700 K	1150 lm	60 lm/W				•	7859-0-A-506-XX	
					3000 K	1200 lm	63 lm/W				•	7859-0-A-887-XX	
					4000 K	1230 lm	64 lm/W				•	7859-0-A-891-XX	
	26 W	N/A	2700 K	1580 lm	60 lm/W	•					7859-0-3-505-XX		
						3000 K	1650 lm	63 lm/W	•			7859-0-3-902-XX	
						4000 K	1690 lm	65 lm/W	•			7859-0-3-905-XX	
						2700 K	1580 lm	60 lm/W		•		7859-0-4-505-XX	
						3000 K	1650 lm	63 lm/W		•		7859-0-4-902-XX	
						4000 K	1690 lm	65 lm/W		•		7859-0-4-905-XX	
				2700 K	1580 lm	60 lm/W			•	7859-0-5-505-XX			
				3000 K	1650 lm	63 lm/W			•	7859-0-5-902-XX			
				4000 K	1690 lm	65 lm/W			•	7859-0-5-905-XX			
				2700 K	1580 lm	60 lm/W				•	7859-0-A-505-XX		
				3000 K	1650 lm	63 lm/W				•	7859-0-A-902-XX		
				4000 K	1690 lm	65 lm/W				•	7859-0-A-905-XX		

*Please contact sales team for special request.