

PLUTO

■ WALL RECESSED



The **PLUTO** range of wall-recessed luminaires is designed for versatile and efficient lighting in various environments. Available with LED light sources in 2700K, 3000K, or 4000K, as well as options for compact fluorescent lamps and an E27 socket for LED retrofit lamps, **PLUTO** offers adaptable solutions for diverse project needs. The **PLUTO-RAMP** model features glare-free, downward light distribution, making it an excellent choice for safe and comfortable pathway and staircase illumination.

The **PLUTO-Flat** version incorporates a unique white ceramic-coated tempered glass that not only provides durability but also ensures soft, even illumination extending beyond the ground to enhance surrounding areas. Its slim, recessed housing allows for seamless integration into thin wall constructions, maintaining aesthetic integrity without compromising performance.

These luminaires are engineered to be reliable and visually appealing, blending into architectural elements while delivering high performance. **PLUTO**'s design makes it a suitable solution for enhancing the ambiance and safety of walkways, outdoor corridors, public spaces, and residential complexes. With multiple configuration options, **PLUTO** caters to the needs of designers and project planners looking for durable and stylish recessed lighting solutions.



www.unilamp.co.th/en/p/pluto

Specification

- Designed, manufactured and tested according to IEC 60598.
- LM6 die cast aluminum housing.
- Stainless steel screws.
- Nano ceramic surface conversion.
- Double layer coating.
- Safety glass cover.
- Post-cured silicone gasket.
- High quality LED module and driver.
- GFR PA6.6 terminal block.
- Weather proof TPE grommet.
- Installation must be carried out according to the enclosed product manual.

Available Color



****Custom colors are available on request.**

PLUTO

1. Body housing

Enhanced LM6 die-cast aluminium housing with 16-Step coating process including nano ceramic film. Low copper content <0.1%

2. Diffuser

Impact resistant safety tempered glass diffuser with micro-pattern arrays. Light spread evenly on the ground.

3. LED

Array of mid power LED from world renowned manufacturer. Module attached on to heat conductive material. 2700K, 3000K and 4000K CRI>80 3-Step SDCM.

4. Driver

High quality LED constant current driver. Complied with Safety and EMC regulations.





Gold Coast – AUSTRALIA



PLUTO



PLUTO
Ramp



PLUTO
Flat



PLUTO

Application Type : Wall recessed

Subgroup : Directed wall recessed light/
General wall recessed light

PLUTO Ramp/ 6015

PLUTO Flat/ 6031

Luminaire Performance

600 - 1310 lm

14 - 26 W

42 - 55 lm/W

Beam Options



Color Temperature





3000K/ 4000K

Controller

On-off/ DALI

Input Voltage

220-240VAC 50/60HZ

	Product Code	Luminaire Wattage	Beam	CCT	Luminaire Lumen	Efficacy	Controller		Ordering Code
									
PLUTO Ramp	OD-6015 	17 W	N/A	3000 K	890 lm	52 lm/W	•		6015-0-3-668-XX
				4000 K	940 lm	55 lm/W			6015-0-3-669-XX
	18 W	N/A	3000 K	870 lm	48 lm/W	•		6015-0-3-867-XX	
			4000 K	930 lm	51 lm/W			6015-0-3-868-XX	
		Side throw	3000 K	800 lm	44 lm/W	•		6015-1-3-867-XX	
			4000 K	860 lm	47 lm/W			6015-1-3-868-XX	
	26 W	N/A	3000 K	1220 lm	46 lm/W	•		6015-0-3-897-XX	
			4000 K	1310 lm	50 lm/W			6015-0-3-898-XX	
		Side throw	3000 K	1120 lm	43 lm/W	•		6015-1-3-897-XX	
			4000 K	1200 lm	46 lm/W			6015-1-3-898-XX	
		N/A	3000 K	1220 lm	46 lm/W		•	6015-0-5-897-XX	
		OD-6031 	14 W	N/A	3000 K	600 lm	42 lm/W	•	
4000 K	600 lm				42 lm/W	6031-0-3-807-XX			

*Please contact sales team for special request.

