


## Art.no. 74604



**An easily located reading luminaire for hospital environments with plastic-coated sprung arm for easy cleaning.**

**Installation** Attached to the hospital ward panel, wall, table or IC rail. Brackets ordered separately, please see accessories.

**Connection** Mains cable 2.0 m, with plug-in transformer 100–240 V, 50/60 Hz. The luminaire is class II.

**Design** Lamp head of cast aluminium with a lamp assembly consisting of 3 light intensive LEDs for reading light and 3 LEDs for night light. A switch on the top of the lamp head turns the night light on/off while the reading light is dimmable via a switch on the handle. The lamp head can be rotated 360°. The S4 arm consists of a plastic-coated spring arm, followed by rigid aluminium tubing that goes into a friction hinge and ends with a 16 mm mounting pin. S7 does not have a friction hinge, instead it features double plastic-coated spring arms. S8 is identical to S7 but adapted for mounting on beds.

**Louvre** The louvre is white frosted as standard but can be provided in different finishes on request.

## Amalia LED

Amalia 9 P S4, with friction hinge

### LIGHT DATA & PERFORMANCE

CCT, K 3000

CRI 90

Energy class, LED module G

### ELECTRICITY & ENCLOSURE

System Wattage 9

### DIMENSIONS

Weight, kg 1,5