


MICRON ADJUSTABLE TRIM IP20

ORDERING CODE: RL59MC22-903018D010



DESCRIPTION

Round shape mounting trim in cast aluminium with springs for trim installation on a ceiling thickness max. 20mm. Luminaire body in cast aluminium and fixing ring in steel. Fixing ring can be installed independently. Easy relamping via removable light head by snap-in catch action. Available in IP20/IP54 versions. Rotable horizontally 350°. IP20: tiltable vertically 0-30°. IP54: tiltable vertically 0-25°.

MOUNTING

Recessed

OPTIC

Reflector + Diffuser.
Narrow, medium and wide beam angle available.

DRIVER OPTIONS

D0 - No Dimming



LIGHT SOURCE AND PERFORMANCE

LIGHT SOURCE: LED Module - COB LED - COB
SDCM: 3-step MacAdam
CCT: 30 - 3000K
CRI: 90
SYSTEM POWER: 12.84
DELIVERED LUMEN: 473.01 lm
IP: 20
LED POWER: 10
NOMINAL LUMEN: 1276 lm
BEAM ANGLE: 18
CANDELA:
ADJUSTABILITY:
OPTIC TYPE

PRODUCT CODE	LIGHT SOURCE CODE	-	CRI	CCT	BEAM ANGLE (BA°)	DRIVER OPTIONS	FINISH
RL59	MC22	-	90	30	18	D0	10 - Black

We reserve the right to change specifications without prior notification.

HONG KONG - LONDON - MILAN - SHANGHAI - NEW YORK