


Art.no. 56948-530

EAN 7320047287947



A robust wall-mounted reading/bed luminaire with high safety for exposed environments.

Installation Luminaire for wall installation.

Connection Connects with 230 V, built-in LED driver. Snap-in terminal block 3x2.5 mm².

Design Enamelled body in steel. Casing of 1 mm white enamelled (RAL9016) aluminium. Pushbutton for off/on and dimming, safe against damage.

Designed by AART Designers

Robust reading luminaire LED G2

Dimming via pushbutton

DESIGN

Turn, ° 25 **RAL** 9016

LIGHT DATA & PERFORMANCE

Lumen output 421 **lm/W** 90
CCT, K 2700 **CRI** 80
SDCM 3 **Lumen maintenance 50 000 h** L96
Lumen maintenance 75 000 h L95 **Lumen maintenance 100 000 h** L94
LED driver, h/max failure % 100000/10 **Energy class, LED module** D

CONTROLS & CONNECTIVITY

Driver brand Tridonic **No of Dali Addresses** 1

ELECTRICITY & ENCLOSURE

Rated supply voltage, V 220-240 **Mains frequency, Hz** 0, 50, 60
Protective class 1 **IP rating** 20
IK rating 10 **System Wattage** 5
Min. ambient temperature, °C -25 **Max. ambient temperature, °C** 25
MCB B10A, pcs 24 **MCB B16A** 38
MCB C10A 40 **MCB C16A** 64
THD, % 40 **Surge protection CM, kV/kA** 2
Surge protection DM, kV/kA 1 **Power factor, 100 %** 0.75

DIMENSIONS

Height, mm 73 **Diameter, mm** 163
Weight, kg 0.5