




## Trackspot V 3Ph.

10/15/20W 927/930/940 24°-60° black

Discover our new technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the minimalist TRACKSPOT V three-phase spotlight, whose light colour (2700K/3000K/400K) and light intensity can be adjusted via dip switches. Thanks to the multi-zoom function, the beam angle is also variable – from 24°, ideal for accent lighting, to 60° for homogeneous illumination. In addition, the high CRI>90 ensures the most lifelike color reproduction possible. Decide in favour of SLVtec today.



## TECHNICAL DATA

|                             |                         |
|-----------------------------|-------------------------|
| Item no.                    | 1007655                 |
| Rotating or tilting         | rotary bar and tiltable |
| IP Code                     | IP20                    |
| Impact resistance class     | IK 05                   |
| Assembly details            | Track Ceiling           |
| Primary nominal voltage     | 220-240V ~50/60Hz       |
| Secondary power / voltage   | 240/380/500 mA          |
| Safety class                | I                       |
| Wattage                     | 20 W                    |
| Minimum ambient temperature | -20 °C                  |
| Maximum ambient temperature | 40 °C                   |
| Level of inrush current     | 9.46 A                  |
| Duration of inrush current  | 1210 µs                 |
| Lumen                       | 1800/1980/1920 lm       |
| Colour temperature          | 2700/3000/4000 Kelvin   |
| Beam angle                  | 24 °                    |
| Color                       | black                   |
| CRI                         | 90                      |
| LXXBXX data                 | L70B50                  |
| Service life                | 50000 h                 |
| Risk Group                  | 1                       |
| Length                      | 14.5 cm                 |

## Light Source

|         |   |
|---------|---|
| 1807499 |  |
|---------|---|

|                |          |
|----------------|----------|
| Height         | 13.5 cm  |
| Diameter       | 7.2 cm   |
| Net weight     | 0.54 kg  |
| Gross weight   | 0.578 kg |
| BIG WHITE Page | 525      |